

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                          | Standard     | Tarkett value                             |
|--------------------------|--------------|---|
| Type of product          | -            | Textile Flooring                          |
| Total thickness          | ASTM F386    | 0.245 " (6.27 mm)                         |
| Flammability             | ASTM E648    | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| Smoke Density            | ASTM E662    | 450 or Less                               |
| Commercial warranty      | -            | Lifetime Limited                          |
| Installation method      | -            | Glue-Down                                 |
| Pattern                  | -            | Input 11083                               |
| Surface treatment        | ASTM F410    | Eco-Ensure(Fluorine-Free Soil Protection) |
| Pattern type             | -            | Linear                                    |
| Format Type              | -            | Tile                                      |
| Construction             | -            | Stratatec® Patterned Syntex®              |
| Pile construction        | -            | Patterned Tipshear                        |
| Gauge                    | -            | 5/64"                                     |
| Stitches/Rows per Inch   | -            | 9.60 /in                                  |
| Pile thickness           | ASTM D5848   | 0.070 " (1.83 mm)                         |
| Average pile height      | -            | 0.185 " (5 mm)                            |
| Fiber System             | -            | Dynex SD® Nylon (Stain resist)            |
| Dye Method               | -            | Solution Dyed                             |
| Secondary backing        | -            | ethos® Modular with Omnicoat Technology™  |
| Primary backing          | -            | Synthetic Non-Woven                       |
| Pattern scale            | -            | Small                                     |
| Pattern match            | -            | No  |
| Soil protection          | -            | Application Rate: 2% of Face Weight       |
| Stain Resistance         | AATCC 175-08 | $\geq 8$                                  |
| Surface Flammability     | -            | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| Electrostatic Propensity | -            | $\leq 3.0$ kV                             |
| Face Weight              | -            | 20 oz/yd <sup>2</sup>                     |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|                                    | Standard | Tarkett value  |
|------------------------------------|----------|--|
| Cradle-to-Cradle                   | -        | Silver   |
| ReStart®                           | -        | Yes  |
| DECLARE                            | -        | Yes  |
| Pre Consumer recycled content      | -        | 23 %   |
| Post Consumer recycled content     | -        | 34 %   |
| CRI Green Label Plus Certification | -        | GLP8320  |
| Third Party Certification NSF-140  | -        | Platinum   |
| Antimicrobial Chemicals            | -        | No antimicrobials (EPA Registered pesticides) added to product |



Input

Input 11083 MOUSEOVER 11605