

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.315 " (8 mm)
Flammability	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Smoke Density	ASTM E662	< 450
Commercial warranty	-	15 year limited
Installation method	-	Glue-Down
Pattern	-	Shadow Velvet 66005
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Format Type	-	Roll
Maximum pile height	-	0.1570 " (3.99 mm)
Construction	-	Woven Velvet Cut & Loop
Stitches/Rows per Inch	-	9.20 /in
Pile thickness	ASTM D5848	0.135 " (3.45 mm)
Average pile height	-	0.155 " (4 mm)
Pile density	-	7430 oz/yd <sup>3</sup>
Fiber System	-	Dynex® Nylon
Dye Method	-	Solution Dyed / Space Dyed
Secondary backing	-	Crossweave Velvet
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	4 "
Pattern repeat width	-	8 "
Soil protection	-	Application Rate: 2% of Face Weight
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	$\leq 3.5$ kV
Colorfastness to Light	AATCC 16E	$\geq 4$ after 60 hours
Length	-	90 ft (27 m)
Width	-	12 ft (3.66 m)
Face Weight	-	28 oz/yd <sup>2</sup>

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %
CRI Green Label Plus Certification	-	GLP100204
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product



Shadow Velvet

Shadow Velvet 66005 WARP BEAM 02998