

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
<b>Pattern</b>	-	Acadia 44069
<b>Pattern type</b>	-	Organic
<b>Format Type</b>	-	Roll
<b>Surface treatment</b>	-	Ensure
<b>Total thickness</b>	-	0.280 " (7.14 mm)
<b>Installation method</b>	-	Glue-Down
<b>Commercial warranty</b>	-	10 year limited
<b>Surface Flammability</b>	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
<b>Electrostatic Propensity</b>	-	0.6 kV
<b>Colorfastness to Light</b>	AATCC 16E	> 4 after 60 hours
<b>Smoke Generation</b>	ASTM E662	< 450
<b>Pattern scale</b>	-	Small
<b>Pattern match</b>	-	Yes
<b>Pattern repeat length</b>	-	31.810 "
<b>Pattern repeat width</b>	-	12 "
<b>Dye Method</b>	-	Solution Dyed
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Primary backing</b>	-	Woven Polypropylene
<b>Secondary backing</b>	-	Super-Lok®
<b>Pile thickness</b>	ASTM D5848	0.185 " (4.75 mm)
<b>Type of product</b>	-	Textile Flooring

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Pre Consumer recycled content</b>	-	0 %
<b>Post Consumer recycled content</b>	-	0 %