

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------------|------------|----------------------------------------|
| Construction | - | Woven Textured Loop |
| Maximum pile height | - | 0.1570 " (3.99 mm) |
| Soil protection | - | Application Rate: 2% of Face Weight |
| Surface Flammability | - | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70 |
| Total thickness | ASTM F386 | 0.290 " (7.37 mm) |
| Electrostatic Propensity | - | ≤ 3.5 kV |
| Stitches/Rows per Inch | - | 9.60 /in |
| Pile thickness | ASTM D5848 | 0.155 " (3.99 mm) |
| Average pile height | - | 0.155 " (4 mm) |
| Pile density | - | 5944 oz/yd ³ |
| Fiber System | - | Dynex SD® Nylon |
| Dye Method | - | Solution Dyed |
| Secondary backing | - | Crossweave® |
| Installation method | - | Glue-Down |
| Pattern | - | Indent 60133 |
| Pattern type | - | Texture |
| Pattern scale | - | Small |
| Pattern match | - | Yes |
| Pattern repeat length | - | 11.49 " |
| Pattern repeat width | - | 0.80 " |
| Format Type | - | Roll |
| Commercial warranty | - | 15 year limited |
| Flammability | ASTM E648 | Class 1 (≥ 0.45 W/cm ²) |
| Smoke Density | ASTM E662 | < 450 |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|-------------------------------------|----------|----------------------------------------------------------------|
| CRI Green Label Plus Certification | - | GLP100204 |
| ReStart® | - | Yes |
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Recycled Content - Production Waste | - | 0 % |
| Post Consumer recycled content | - | 0 % |