

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CLASSIFICATION

|                            | Standard  | Tarkett value                             |
|----------------------------|-----------|---|
| <b>Surface treatment</b>   | -         | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Flammability</b>        | ASTM E648 | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Total thickness</b>     | ASTM F386 | 0.245 " (6.3 mm)                          |
| <b>Smoke Density</b>       | ASTM E662 | 450 or Less                               |
| <b>Pattern</b>             | -         | Maelstrom 04849                           |
| <b>Pattern type</b>        | -         | Geometric                                 |
| <b>Format Type</b>         | -         | Tile                                      |
| <b>Commercial warranty</b> | -         | Lifetime Limited                          |

### CHARACTERISTICS

|  | Standard | Tarkett value                             |
|--|----------|---|
| <b>Total thickness</b>                     | -        | 0.245 " (6.3 mm)                          |
| <b>Pile thickness</b>                      | ISO 1766 | 0.085 " (2.18 mm)                         |
| <b>Fiber System</b>                        | ISO 2424 | Dynex SD® Nylon (Stain resist)            |
| <b>Format Type</b>                         | -        | Tile                                      |
| <b>Commercial warranty</b>                 | -        | Lifetime Limited                          |
| <b>Construction Process</b>                | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>                 | -        | Glue-Down                                 |
| <b>Surface treatment</b>                   | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>                   | ISO 2424 | ethos® Modular with Omniccoat Technology™ |
| <b>Dye Method</b>                          | -        | Solution dyed                             |
| <b>Primary backing</b>                     | -        | Synthetic Non-Woven                       |
| <b>Pile construction</b>                   | -        | Patterned loop pile                       |
| <b>Gauge</b>                               | -        | 5/64"                                     |
| <b>Face Weight</b>                         | -        | 18 oz/yd <sup>2</sup>                     |
| <b>ReStart®</b>                            | -        | Yes                                       |
| <b>DECLARE</b>                             | -        | Yes                                       |
| <b>Recycled Content - Production Waste</b> | -        | 24 %                                      |
| <b>Post Consumer recycled content</b>      | -        | 35 %                                      |
| <b>Cradle-to-Cradle</b>                    | -        | Silver                                    |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value                             |
|---------------------------------|----------|---|
| <b>Flammability</b>             | -        | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Electrostatic Propensity</b> | -        | $\leq 3.0$ kV                             |
| <b>Is cutable</b>               | -        | No  |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value  |
|--|----------|--|
| <b>Cradle-to-Cradle</b>                    | -        | Silver   |
| <b>ReStart®</b>                            | -        | Yes  |
| <b>CRI Green Label Plus Certification</b>  | -        | GLP8320  |
| <b>DECLARE</b>                             | -        | Yes  |
| <b>Recycled Content - Production Waste</b> | -        | 24 %   |
| <b>Third Party Certification NSF-140</b>   | -        | Platinum   |
| <b>Antimicrobial Chemicals</b>             | -        | No antimicrobials (EPA Registered pesticides) added to product |
| <b>Post Consumer recycled content</b>      | -        | 35 %   |

## CHARACTERISTICS & TECHNICAL PERFORMANCE

|                                 | Standard     | Tarkett value                             |
|---------------------------------|--------------|---|
| <b>Total thickness</b>          | ASTM F386    | 0.245 " (6.3 mm)                          |
| <b>Type of product</b>          | -            | Textile Flooring                          |
| <b>Flammability</b>             | ASTM E648    | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| <b>Smoke Density</b>            | ASTM E662    | 450 or Less                               |
| <b>Pattern</b>                  | -            | Maelstrom 04849                           |
| <b>Commercial warranty</b>      | -            | Lifetime Limited                          |
| <b>Surface treatment</b>        | -            | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>      | -            | Glue-Down                                 |
| <b>Pattern type</b>             | -            | Geometric                                 |
| <b>Format Type</b>              | -            | Tile                                      |
| <b>Construction</b>             | -            | Stratatec® Patterned Loop                 |
| <b>Soil protection</b>          | -            | Application Rate: 2% of Face Weight       |
| <b>Stitches/Rows per Inch</b>   | -            | 9.60 /in                                  |
| <b>Pile thickness</b>           | ASTM D5848   | 0.085 " (2.18 mm)                         |
| <b>Average pile height</b>      | -            | 0.185 " (5 mm)                            |
| <b>Fiber System</b>             | -            | Dynex SD® Nylon (Stain resist)            |
| <b>Dye Method</b>               | -            | Solution dyed                             |
| <b>Secondary backing</b>        | -            | ethos® Modular with Omnicat Technology™   |
| <b>Primary backing</b>          | -            | Synthetic Non-Woven                       |
| <b>Pattern repeat length</b>    | -            | 99.20 "                                   |
| <b>Pattern repeat width</b>     | -            | 72 "                                      |
| <b>Stain Resistance</b>         | AATCC 175-08 | $\geq 8$                                  |
| <b>Pile construction</b>        | -            | Patterned loop pile                       |
| <b>Surface Flammability</b>     | -            | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| <b>Electrostatic Propensity</b> | -            | $\leq 3.0$ kV                             |
| <b>Gauge</b>                    | -            | 5/64"                                     |