

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
<b>Construction Process</b>	ISO 2424	TUFTED
<b>Total thickness</b>	-	0.245 " (6.3 mm)
<b>Installation method</b>	-	Glue-Down
<b>Commercial warranty</b>	-	Lifetime Limited
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Secondary backing</b>	ISO 2424	ethos® Modular with Omniccoat Technology™
<b>Pile construction</b>	-	Patterned loop pile
<b>Gauge</b>	-	5/64"
<b>Pile thickness</b>	ISO 1766	0.105 " (2.64 mm)
<b>Face Weight</b>	-	20 oz/yd²
<b>Dye Method</b>	-	Solution dyed
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Fiber System</b>	ISO 2424	Dynex SD® Nylon
<b>Cradle-to-Cradle</b>	-	Silver
<b>DECLARE</b>	-	Yes

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Flammability</b>	-	Class 1 ( $\geq 0.45$ W/cm²)
<b>Electrostatic Propensity</b>	-	$\leq 3.0$ kV
<b>Is cuttable</b>	-	No
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Total thickness</b>	-	0.245 " (6.3 mm)
<b>Installation method</b>	-	Glue-Down

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Cradle-to-Cradle</b>	-	Silver
<b>CRI Green Label Plus Certification</b>	-	GLP8320
<b>ReStart®</b>	-	Yes
<b>DECLARE</b>	-	Yes
<b>Third Party Certification NSF-140</b>	-	Platinum
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
<b>Recycled Content - Production Waste</b>	-	23 %
<b>Post Consumer recycled content</b>	-	34 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Construction	Standard	Tarkett value Stratatec® Patterned Loop
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥8
Pile construction	-	Patterned loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Total thickness	ASTM F386	0.245 " (6.3 mm)
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"
Stitches/Rows per Inch	-	10 /in
Pile thickness	ASTM D5848	0.105 " (2.64 mm)
Average pile height	-	0.185 " (5 mm)
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omniccoat Technology™
Primary backing	-	Synthetic Non-Woven
Installation method	-	Glue-Down
Pattern	-	Dot Matrix 04852
Pattern type	-	Texture
Pattern scale	-	Medium
Pattern match	-	No
Pattern repeat length	-	73.80 "
Pattern repeat width	-	72 "
Commercial warranty	-	Lifetime Limited
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm²)
Smoke Density	ASTM E662	450 or Less
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring