

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Construction Process | ISO 2424 | TUFTED |
| Total thickness | - | 0.245 " (6.27 mm) |
| Installation method | - | Glue-Down |
| Format Type | - | Tile |
| Items per box | - | 15 |
| Surface per box | - | 6.667 sq. yd |
| Box per pallet | - | 30 |
| Commercial warranty | - | Lifetime Limited |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular with Omnicoat Technology™ |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Pile thickness | ISO 1766 | 0.090 " (2.34 mm) |
| Face Weight | - | 20 oz/yd ² |
| Pile density | ISO 8543 | 122.88 oz/yd ³ |
| Dye Method | - | Solution dyed |
| Primary backing | - | Synthetic Non-Woven |
| Fiber System | ISO 2424 | Dynex SD® Nylon (Stain resist) |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|---------------------------------|----------|-------------------------------------|
| Flammability | - | Class 1 (≥ 0.45 W/cm ²) |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Is cuttable | - | No |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|--|----------|--|
| Cradle-to-Cradle | - | Silver |
| CRI Green Label Plus Certification | - | GLP8320 |
| ReStart® | - | Yes |
| DECLARE | - | Yes |
| Third Party Certification NSF-140 | - | Platinum |
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Recycled Content - Production Waste | - | 23 % |
| Post Consumer recycled content | - | 34 % |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|---------------------------------|--------------|---|
| Construction | Standard | Tarkett value |
| | - | Stratec® Patterned Loop |
| Soil protection | - | Application Rate: 2% of Face Weight |
| Pile construction | - | Patterned loop pile |
| Stain Resistance | AATCC 175-08 | ≥8 |
| Surface Flammability | - | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70 |
| Total thickness | ASTM F386 | 0.245 " (6.27 mm) |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Gauge | - | 5/64" |
| Stitches/Rows per Inch | - | 9.60 /in |
| Pile thickness | ASTM D5848 | 0.090 " (2.34 mm) |
| Average pile height | - | 0.140 " (4 mm) |
| Pile density | - | 122.88 oz/yd ³ |
| Fiber System | - | Dynex SD® Nylon (Stain resist) |
| Dye Method | - | Solution dyed |
| Secondary backing | - | ethos® Modular with Omnicoat Technology™ |
| Primary backing | - | Synthetic Non-Woven |
| Installation method | - | Glue-Down |
| Pattern | - | ColorMap 11130 |
| Pattern type | - | Organic |
| Pattern scale | - | Large |
| Pattern match | - | No |
| Format Type | - | Tile |
| Commercial warranty | - | Lifetime Limited |
| Flammability | ASTM E648 | Class 1 (≥ 0.45 W/cm ²) |
| Smoke Density | ASTM E662 | 450 or Less |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Type of product | - | Textile Flooring |
| Length | - | 24 " |
| Width | - | 24 " |
| Items per box | - | 15 |