

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

TECHNICAL PERFORMANCE & CHARACTERISTICS

	Standard	Tarkett value
Professional warranty (in years)	-	Lifetime Limited
Pattern	-	Andros G0015
Pattern type	-	Organic
Format Type	-	Tile
Dye Method	-	Solution Dyed
Fiber System	-	TDX® Nylon
Primary backing	-	Synthetic Non-Woven
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Stitch Rate	-	8.40 /in
Gauge Rate	-	1/10"
Total thickness	ASTM F386	0.245 " (6.25 mm)
Pile thickness	ASTM D5848	0.100 " (2.50 mm)
Pile height average	-	0.185 " (5 mm)
Face Weight	-	31 oz/yd²
Tuft Density	-	84 /in² (0.1 /cm²)
Installation method	-	Glue-Down
Flooring Radiant Panel	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E662	< 450

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
CRI Green Label Plus Certification	-	GLP8320
Cradle-to-Cradle	-	Silver
Pre Consumer recycled content	-	29 %
Post Consumer recycled content	-	34.8 %
Third Party Certification NSF-140	-	Platinum