

**TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS**

**CHARACTERISTICS**

	Standard	Tarkett value
<b>Primary backing</b>	-	Synthetic Non-Woven

**TECHNICAL PERFORMANCE & CHARACTERISTICS**

	Standard	Tarkett value
<b>Professional warranty (in years)</b>	-	Lifetime Limited
<b>Pattern</b>	-	Brushline 06255
<b>Pattern type</b>	-	Linear
<b>Format Type</b>	-	Tile
<b>Dye Method</b>	-	Solution Dyed
<b>Fiber System</b>	-	TDX® Nylon
<b>Secondary backing</b>	-	Ecoply
<b>Pile height average</b>	-	0.155 " (4 mm)
<b>Tuft Density</b>	-	115.80 /in² (0.1 /cm²)
<b>Installation method</b>	-	Glue-Down
<b>Flooring Radiant Panel</b>	ASTM E648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
<b>Smoke Generation</b>	ASTM E662	<450

**SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY**

	Standard	Tarkett value
<b>CRI Green Label Plus Certification</b>	-	GLP5288