

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.200 " (5.11 mm)
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less
Commercial warranty	-	Lifetime Limited
Installation method	-	Glue-Down
Pattern	-	Airspace 11352
Surface treatment	ASTM F410	Dura Tech®
Pattern type	-	Geometric
Format Type	-	Tile
Construction	-	Accuweave® Patterned Loop
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Stitches/Rows per Inch	-	9.80 /in
Pile thickness	ASTM D5848	0.070 " (1.73 mm)
Average pile height	-	0.140 " (4 mm)
Fiber System	-	Antron Lumena® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Primary backing	-	Synthetic Non-Woven
Pattern scale	-	Large
Pattern match	-	Yes
Pattern repeat length	-	9.10 "
Pattern repeat width	-	72 "
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	≥ 8
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.0 kV
Face Weight	-	14 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
ReStart®	-	Yes
DECLARE	-	Yes
Pre Consumer recycled content	-	25 %
Post Consumer recycled content	-	36 %
CRI Green Label Plus Certification	-	GLP8320

	Standard	Tarkett value
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product