

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	< 450
Commercial warranty	-	15 year limited
Installation method	-	Glue-Down
Pattern	-	Velvet Line 66007
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Linear
Format Type	-	Roll
Maximum pile height	-	0.2370 " (6.02 mm)
Construction	-	Woven Velvet Cut & Loop
Stitches/Rows per Inch	-	8.80 /in
Pile thickness	ASTM D5848	0.185 " (4.70 mm)
Average pile height	-	0.195 " (5 mm)
Minimum pile height	-	0.1570 " (3.99 mm)
Pile density	-	7747 oz/yd ³
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	Crossweave Velvet
Pattern scale	-	Small
Pattern match	-	Yes
Pattern repeat length	-	4 "
Pattern repeat width	-	0.13 "
Soil protection	-	Application Rate: 2% of Face Weight
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.5 kV
Length	-	90 ft (27 m)
Width	-	12 ft (3.66 m)
Face Weight	-	40 oz/yd ²

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
ReStart®	-	Yes
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %
CRI Green Label Plus Certification	-	GLP100204
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product



Velvet Lines

Velvet Line 66007 CHINCHILLA 03055