

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Construction Process | ISO 2424 | TUFTED |
| Total thickness | - | 0.080 " (2.03 mm) |
| Installation method | - | Glue-Down |
| Format Type | - | Roll |
| Commercial warranty | - | 10 year limited |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | Super-Lok® |
| Pile construction | - | Patterned Tipshear |
| Gauge | - | 5/64" |
| Pile thickness | ISO 1766 | 0.195 " (5 mm) |
| Face Weight | - | 26 oz/yd ² |
| Pile density | ISO 8543 | 5540 oz/yd ³ |
| Dye Method | - | Solution dyed |
| Primary backing | - | Woven Polypropylene |
| Fiber System | ISO 2424 | Dynex SD® Nylon |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|---------------------------------|----------|---|
| Flammability | - | Class 1 (≥ 0.45 W/cm ²) |
| Electrostatic Propensity | - | ≤ 3.5 kV |
| Colorfastness to Light | - | ≥ 4 after 100 hours |
| Is cutable | - | Yes |
| Total thickness | - | 0.080 " (2.03 mm) |
| Installation method | - | Glue-Down |
| Format Type | - | Roll |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|--|----------|--|
| CRI Green Label Plus Certification | - | GLP0025 |
| ReStart® | - | Yes |
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Recycled Content - Production Waste | - | 0 % |
| Post Consumer recycled content | - | 0 % |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|----------------------------|----------|-----------------|
| Maximum pile height | - | 0.1970 " (5 mm) |

| | Standard | Tarkett value |
|---------------------------------|--------------|---|
| Soil protection | - | Application Rate: 2% of Face Weight |
| Pile construction | - | Patterned Tipshear |
| Stain Resistance | AATCC 175-08 | ≥8 |
| Surface Flammability | - | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70 |
| Total thickness | ASTM F386 | 0.080 " (2.03 mm) |
| Electrostatic Propensity | - | ≤ 3.5 kV |
| Gauge | - | 5/64" |
| Colorfastness to Light | AATCC 16E | ≥ 4 after 100 hours |
| Stitches/Rows per Inch | - | 12.60 /in |
| Pile thickness | ASTM D5848 | 0.195 " (5 mm) |
| Minimum pile height | - | 0.0790 " (2.01 mm) |
| Pile density | - | 5540 oz/yd ³ |
| Fiber System | - | Dynex SD® Nylon |
| Dye Method | - | Solution dyed |
| Secondary backing | - | Super-Lok® |
| Primary backing | - | Woven Polypropylene |
| Installation method | - | Glue-Down |
| Pattern | - | Sunshadow 40047 |
| Pattern type | - | Organic |
| Pattern scale | - | Medium |
| Pattern match | - | Yes |
| Pattern repeat length | - | 31.75 " |
| Pattern repeat width | - | 18.75 " |
| Format Type | - | Roll |
| Commercial warranty | - | 10 year limited |
| Flammability | ASTM E648 | Class 1 (≥ 0.45 W/cm ²) |
| Smoke Density | ASTM E662 | < 450 |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Type of product | - | Textile Flooring |
| Length | - | 1800 " |
| Width | - | 150 " |