

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Total thickness	ASTM F386	0.080 " (2.03 mm)
Flammability	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
Smoke Density	ASTM E662	< 450
Commercial warranty	-	20 year limited
Installation method	-	Glue-Down
Pattern	-	Sunshadow 40047
Surface treatment	ASTM F410	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern type	-	Organic
Format Type	-	Roll
Maximum pile height	-	0.1970 " (5 mm)
Pile construction	-	Patterned Tipshear
Gauge	-	5/64"
Stitches/Rows per Inch	-	12.60 /in
Minimum pile height	-	0.0790 " (2.01 mm)
Pile density	-	5540 oz/yd <sup>3</sup>
Fiber System	-	Dynex SD® Nylon
Dye Method	-	Solution Dyed
Secondary backing	-	LifeLONG®
Primary backing	-	Woven Polypropylene
Soil protection	-	Application Rate: 2% of Face Weight
Stain Resistance	AATCC 175-08	$\geq 8$
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	$\leq 3.5$ kV
Colorfastness to Light	AATCC 16E	$\geq 4$ after 100 hours
Length	-	150 ft (46 m)
Width	-	12.5 ft (3.81 m)

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Pre Consumer recycled content	-	0 %
Post Consumer recycled content	-	0 %