

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Total thickness	ASTM F386	0.200 " (5.1 mm)
Smoke Density	ASTM E662	450 or Less
Pattern	-	Offset 11338
Pattern type	-	Organic
Commercial warranty	-	Lifetime Limited

CHARACTERISTICS

	Standard	Tarkett value
Total thickness	-	0.200 " (5.1 mm)
Pile thickness	ISO 1766	0.055 " (1.40 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Commercial warranty	-	Lifetime Limited
Construction Process	ISO 2424	TUFTED
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omniccoat Technology™
Dye Method	-	Solution dyed
Primary backing	-	Synthetic Non-Woven
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Face Weight	-	14 oz/yd ²
Pile density	ISO 8543	125.40 oz/yd ³
ReStart®	-	Yes
DECLARE	-	Yes
Recycled Content - Production Waste	-	25 %
Post Consumer recycled content	-	36 %
Cradle-to-Cradle	-	Silver

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Flammability	-	Class 1 (≥ 0.45 W/cm ²)
Electrostatic Propensity	-	≤ 3.0 kV
Is cuttable	-	No

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	Standard	Tarkett value Silver
ReStart®	-	Yes
CRI Green Label Plus Certification	-	GLP8320
DECLARE	-	Yes
Recycled Content - Production Waste	-	25 %
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Post Consumer recycled content	-	36 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Total thickness	ASTM F386	0.200 " (5.1 mm)
Type of product	-	Textile Flooring
Flammability	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Smoke Density	ASTM E662	450 or Less
Pattern	-	Offset 11338
Commercial warranty	-	Lifetime Limited
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Organic
Construction	-	Stratatec® Patterned Loop
Soil protection	-	Application Rate: 2% of Face Weight
Stitches/Rows per Inch	-	9.80 /in
Pile thickness	ASTM D5848	0.055 " (1.40 mm)
Average pile height	-	0.140 " (4 mm)
Pile density	-	125.40 oz/yd ³
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omnicat Technology™
Primary backing	-	Synthetic Non-Woven
Pattern match	-	No
Pattern repeat length	-	132.25 "
Pattern repeat width	-	72 "
Stain Resistance	AATCC 175-08	≥ 8
Pile construction	-	Patterned loop pile
Surface Flammability	-	Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"