

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                          | Standard     | Tarkett value                             |
|--------------------------|--------------|---|
| Type of product          | -            | Textile Flooring                          |
| Total thickness          | ASTM F386    | 0.265 " (6.76 mm)                         |
| Flammability             | ASTM E648    | Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> ) |
| Smoke Density            | ASTM E662    | < 450                                     |
| Commercial warranty      | -            | 10 year limited                           |
| Installation method      | -            | Glue-Down                                 |
| Pattern                  | -            | Radiance K0101                            |
| Surface treatment        | ASTM F410    | Eco-Ensure(Fluorine-Free Soil Protection) |
| Pattern type             | -            | Organic                                   |
| Format Type              | -            | Roll                                      |
| Construction             | -            | Patterned Symtex                          |
| Gauge                    | -            | 1/10"                                     |
| Stitches/Rows per Inch   | -            | 9.60 /in                                  |
| Average pile height      | -            | 0.255 " (7 mm)                            |
| Pile density             | -            | 6275 oz/yd <sup>3</sup>                   |
| Fiber System             | -            | Dynex SD® Nylon                           |
| Dye Method               | -            | Solution Dyed                             |
| Secondary backing        | -            | Super-Lok®                                |
| Primary backing          | -            | Woven Polypropylene                       |
| Pattern scale            | -            | Large                                     |
| Pattern match            | -            | Yes                                       |
| Pattern repeat length    | -            | 76.88 "                                   |
| Pattern repeat width     | -            | 72 "                                      |
| Soil protection          | -            | Application Rate: 2% of Face Weight       |
| Stain Resistance         | AATCC 175-08 | $\geq 8$                                  |
| Surface Flammability     | -            | Meets CAN/CGSB-4.2 No.27.6/DOC FF 1-70    |
| Electrostatic Propensity | -            | $\leq 3.5$ kV                             |
| Colorfastness to Light   | AATCC 16E    | $\geq 4$ after 100 hours                  |
| Length                   | -            | 150 ft (46 m)                             |
| Width                    | -            | 12 ft (3.66 m)                            |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|                                | Standard | Tarkett value |
|--------------------------------|----------|---------------|
| Pre Consumer recycled content  | -        | 0 %           |
| Post Consumer recycled content | -        | 0 %           |