

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Cradle-to-Cradle</b>	-	Silver
<b>CRI Green Label Plus Certification</b>	-	GLP8320
<b>Third Party Certification NSF-140</b>	-	Platinum
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
<b>Recycled Content - Production Waste</b>	-	23.9 %
<b>Post Consumer recycled content</b>	-	34.8 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Construction</b>	-	Stratatec® Patterned Syntex®
<b>Soil protection</b>	-	Application Rate: 2% of Face Weight
<b>Stain Resistance</b>	AATCC 175-08	≥8
<b>Pile construction</b>	-	Patterned Tipshear
<b>Surface Flammability</b>	-	PASS
<b>Electrostatic Propensity</b>	-	1.8 kV
<b>Gauge</b>	-	5/64"
<b>Colorfastness to Light</b>	AATCC 16E	≥ 4 after 100 hours
<b>Stitches/Rows per Inch</b>	-	9.60 /in
<b>Pile thickness</b>	ASTM D5848	0.185 " (4.75 mm)
<b>Average pile height</b>	-	0.185 " (5 mm)
<b>Pile density</b>	-	14233 oz/yd <sup>3</sup>
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Dye Method</b>	-	Solution dyed
<b>Secondary backing</b>	-	ethos® Modular with Omnicoat Technology™
<b>Primary backing</b>	-	Synthetic Non-Woven
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Suede Tones 11531
<b>Pattern type</b>	-	Organic
<b>Pattern repeat length</b>	-	88.75 "
<b>Pattern repeat width</b>	-	72 "
<b>Commercial warranty</b>	-	Lifetime Limited
<b>Flammability</b>	ASTM E648	Class 1 (≥ 0.45 W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	450 or Less