

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|----------------------------|----------|---|
| Total thickness | - | 0.250 " (6.4 mm) |
| Pile thickness | ISO 1766 | 0.185 " (4.75 mm) |
| Fiber System | ISO 2424 | Dynex SD® Nylon |
| Format Type | - | Tile |
| Installation method | - | Glue-Down |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular with Omnicoat Technology™ |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Dye Method | - | Solution dyed |
| Product Material | - | Tufted |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------|----------|---------------|
| Is cuttable | - | No |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|-------------------------------|------------|---|
| Total thickness | ASTM F386 | 0.250 " (6.4 mm) |
| Type of product | - | Textile Flooring |
| Pattern | - | Thread Craft 11569 |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method | - | Glue-Down |
| Pattern type | - | Geometric |
| Format Type | - | Tile |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Stitches/Rows per Inch | - | 8.10 /in |
| Pile thickness | ASTM D5848 | 0.185 " (4.75 mm) |
| Average pile height | - | 0.185 " (5 mm) |
| Fiber System | - | Dynex SD® Nylon |
| Dye Method | - | Solution dyed |
| Secondary backing | - | ethos® Modular with Omnicoat Technology™ |
| Pattern repeat length | - | 44.44 " |
| Pattern repeat width | - | 18.13 " |