

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Total thickness	ASTM F386	0.250 " (6.4 mm)
Pattern	-	Thread Craft 11569
Pattern type	-	Geometric
Format Type	-	Tile

CHARACTERISTICS

	Standard	Tarkett value
Total thickness	-	0.250 " (6.4 mm)
Pile thickness	ISO 1766	0.185 " (4.75 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Format Type	-	Tile
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Dye Method	-	Solution dyed
Product Material	-	Tufted
Pile construction	-	Patterned loop pile
Gauge	-	5/64"

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	No

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Total thickness	ASTM F386	0.250 " (6.4 mm)
Type of product	-	Textile Flooring
Pattern	-	Thread Craft 11569
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Geometric
Format Type	-	Tile
Stitches/Rows per Inch	-	8.10 /in
Pile thickness	ASTM D5848	0.185 " (4.75 mm)
Average pile height	-	0.185 " (5 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)

	Standard	Tarkett value
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omniccoat Technology™
Pattern repeat length	-	44.44 "
Pattern repeat width	-	18.13 "
Pile construction	-	Patterned loop pile
Gauge	-	5/64"