

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Total thickness	ASTM F386	0.220 " (5.6 mm)
Pattern	-	Earthbound 11573
Pattern type	-	Organic
Format Type	-	Tile

CHARACTERISTICS

	Standard	Tarkett value
Total thickness	-	0.220 " (5.6 mm)
Pile thickness	ISO 1766	0.140 " (3.56 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Format Type	-	Tile
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omniccoat Technology™
Dye Method	-	Solution dyed
Product Material	-	Tufted
Pile construction	-	Patterned loop pile
Gauge	-	5/64"

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	No

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Total thickness	ASTM F386	0.220 " (5.6 mm)
Type of product	-	Textile Flooring
Pattern	-	Earthbound 11573
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Organic
Format Type	-	Tile
Stitches/Rows per Inch	-	10.80 /in
Pile thickness	ASTM D5848	0.140 " (3.56 mm)
Average pile height	-	0.140 " (4 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)

	Standard	Tarkett value
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omniccoat Technology™
Pattern repeat length	-	111.10 "
Pattern repeat width	-	72 "
Pile construction	-	Patterned loop pile
Gauge	-	5/64"