

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
<b>Total thickness</b>	-	0.250 " (6.4 mm)
<b>Pile thickness</b>	ISO 1766	0.140 " (3.56 mm)
<b>Fiber System</b>	ISO 2424	Dynex SD® Nylon
<b>Format Type</b>	-	Tile
<b>Construction Process</b>	ISO 2424	TUFTED
<b>Installation method</b>	-	Glue-Down
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Secondary backing</b>	ISO 2424	ethos® Modular with Omnicoat Technology™
<b>Pile construction</b>	-	Patterned loop pile
<b>Gauge</b>	-	5/64"
<b>Dye Method</b>	-	Solution dyed
<b>Product Material</b>	-	Tufted

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Is cutable</b>	-	No

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Total thickness</b>	ASTM F386	0.250 " (6.4 mm)
<b>Type of product</b>	-	Textile Flooring
<b>Pattern</b>	-	Corollary 11577
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Installation method</b>	-	Glue-Down
<b>Pattern type</b>	-	Geometric
<b>Format Type</b>	-	Tile
<b>Pile construction</b>	-	Patterned loop pile
<b>Gauge</b>	-	5/64"
<b>Stitches/Rows per Inch</b>	-	9.90 /in
<b>Pile thickness</b>	ASTM D5848	0.140 " (3.56 mm)
<b>Average pile height</b>	-	0.140 " (4 mm)
<b>Fiber System</b>	-	Dynex SD® Nylon
<b>Dye Method</b>	-	Solution dyed
<b>Secondary backing</b>	-	ethos® Modular with Omnicoat Technology™
<b>Pattern repeat length</b>	-	187.87 "
<b>Pattern repeat width</b>	-	72 "



Corollary  
Corollary 11577 GREENBUC 39409