

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Construction Process	ISO 2424	TUFTED
Total thickness	-	0.315 " (7.95 mm)
Installation method	-	Glue-Down
Format Type	-	Tile
Items per box	-	15
Surface per box	-	6.667 sq. yd
Box per pallet	-	30
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	Modular Flex Aire® Cushion
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Pile thickness	ISO 1766	0.140 " (3.56 mm)
Dye Method	-	Solution dyed
Product Material	-	Tufted
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	No

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Pile construction	-	Patterned loop pile
Total thickness	ASTM F386	0.315 " (7.95 mm)
Gauge	-	5/64"
Stitches/Rows per Inch	-	9.90 /in
Pile thickness	ASTM D5848	0.140 " (3.56 mm)
Average pile height	-	0.140 " (4 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	Modular Flex Aire® Cushion
Installation method	-	Glue-Down
Pattern	-	Spin-Off 11578
Pattern type	-	Geometric
Pattern repeat width	-	1828.80 "
Format Type	-	Tile
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Type of product	-	Textile Flooring



Spin-Off
Spin-Off 11578 VARIFORM 39402

	Standard	Tarkett value
--	----------	---------------

Items per box	-	15
----------------------	---	----