

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Smoke Density	ASTM E662	< 450
Pattern	-	Fallow Ground 11598
Pattern type	-	Geometric
Format Type	-	Tile

CHARACTERISTICS

	Standard	Tarkett value
Pile thickness	ISO 1766	0.140 " (3.58 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Format Type	-	Tile
Construction Process	ISO 2424	TUFTED
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Dye Method	-	Solution dyed
Product Material	-	Tufted
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Post Consumer recycled content	-	28 %
Cradle-to-Cradle	-	Silver

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Electrostatic Propensity	-	≤ 3.0 kV
Colorfastness to Light	-	≥ 4 after 100 hours
Is cuttable	-	Yes

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Cradle-to-Cradle	-	Silver
Third Party Certification NSF-140	-	Platinum
Antimicrobial Chemicals	-	No antimicrobials (EPA Registered pesticides) added to product
Post Consumer recycled content	-	28 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	Standard	Textile Flooring
Smoke Density	ASTM E662	< 450
Pattern	-	Fallow Ground 11598
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Geometric
Format Type	-	Tile
Soil protection	-	Application Rate: 2% of Face Weight
Colorfastness to Light	AATCC 16E	≥ 4 after 100 hours
Stitches/Rows per Inch	-	11 /in
Pile thickness	ASTM D5848	0.140 " (3.58 mm)
Maximum pile height	-	0.1410 " (3.58 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omniccoat Technology™
Pattern repeat length	-	24.16 "
Pattern repeat width	-	72 "
Stain Resistance	AATCC 175-08	≥8
Pile construction	-	Patterned loop pile
Surface Flammability	-	PASS
Electrostatic Propensity	-	≤ 3.0 kV
Gauge	-	5/64"