

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

	Standard	Tarkett value
<b>Total thickness</b>	-	0.375 " (9.5 mm)
<b>Fiber System</b>	ISO 2424	Dynex SD® Nylon (Stain resist)
<b>Format Type</b>	-	Tile
<b>Construction Process</b>	ISO 2424	TUFTED
<b>Installation method</b>	-	Glue-Down
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Secondary backing</b>	ISO 2424	ethos® Modular
<b>Pile construction</b>	-	Patterned loop pile
<b>Gauge</b>	-	5/64"
<b>Dye Method</b>	-	Solution dyed
<b>Product Material</b>	-	Tufted
<b>Cradle-to-Cradle</b>	-	Silver

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Electrostatic Propensity</b>	-	≤ 3.0 kV
<b>Colorfastness to Light</b>	-	≥ 4 after 100 hours
<b>Is cuttable</b>	-	No

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Cradle-to-Cradle</b>	-	Silver
<b>Third Party Certification NSF-140</b>	-	Platinum
<b>Antimicrobial Chemicals</b>	-	No antimicrobials (EPA Registered pesticides) added to product
<b>Post Consumer recycled content</b>	-	28 %

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Total thickness</b>	ASTM F386	0.375 " (9.5 mm)
<b>Type of product</b>	-	Textile Flooring
<b>Pattern</b>	-	Lush Garden 11599
<b>Smoke Density</b>	ASTM E662	< 450
<b>Surface treatment</b>	-	Eco-Ensure(Fluorine-Free Soil Protection)
<b>Installation method</b>	-	Glue-Down
<b>Pattern type</b>	-	Organic
<b>Format Type</b>	-	Tile
<b>Soil protection</b>	-	Application Rate: 2% of Face Weight

	Standard	Tarkett value
<b>Maximum pile height</b>	-	0.1410 " (3.58 mm)
<b>Stain Resistance</b>	AATCC 175-08	≥8
<b>Pile construction</b>	-	Patterned loop pile
<b>Surface Flammability</b>	-	PASS
<b>Electrostatic Propensity</b>	-	≤ 3.0 kV
<b>Gauge</b>	-	5/64"
<b>Colorfastness to Light</b>	AATCC 16E	≥ 4 after 100 hours
<b>Stitches/Rows per Inch</b>	-	10 /in
<b>Fiber System</b>	-	Dynex SD® Nylon (Stain resist)
<b>Dye Method</b>	-	Solution dyed
<b>Secondary backing</b>	-	ethos® Modular
<b>Pattern repeat length</b>	-	49.10 "
<b>Pattern repeat width</b>	-	72 "