

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.140 " (3.58 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex SD® Nylon (Stain resist)            |
| <b>Format Type</b>          | -        | Tile                                      |
| <b>Construction Process</b> | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | ethos® Modular with Omnicoat Technology™  |
| <b>Pile construction</b>    | -        | Patterned loop pile                       |
| <b>Gauge</b>                | -        | 5/64"                                     |
| <b>Dye Method</b>           | -        | Solution dyed                             |
| <b>Product Material</b>     | -        | Tufted                                    |
| <b>Cradle-to-Cradle</b>     | -        | Silver                                    |

### TECHNICAL PERFORMANCE

|                                 | Standard | Tarkett value       |
|---------------------------------|----------|---------------------|
| <b>Electrostatic Propensity</b> | -        | ≤ 3.0 kV            |
| <b>Colorfastness to Light</b>   | -        | ≥ 4 after 100 hours |
| <b>Is cuttable</b>              | -        | Yes                 |

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

|  | Standard | Tarkett value  |
|--|----------|--|
| <b>Cradle-to-Cradle</b>                  | -        | Silver   |
| <b>Third Party Certification NSF-140</b> | -        | Platinum   |
| <b>Antimicrobial Chemicals</b>           | -        | No antimicrobials (EPA Registered pesticides) added to product |
| <b>Post Consumer recycled content</b>    | -        | 28 %   |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                            | Standard  | Tarkett value                             |
|----------------------------|-----------|---|
| <b>Type of product</b>     | -         | Textile Flooring                          |
| <b>Pattern</b>             | -         | Idyllic Lands 11601                       |
| <b>Smoke Density</b>       | ASTM E662 | < 450                                     |
| <b>Surface treatment</b>   | -         | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b> | -         | Glue-Down                                 |
| <b>Pattern type</b>        | -         | Geometric                                 |
| <b>Format Type</b>         | -         | Tile                                      |
| <b>Soil protection</b>     | -         | Application Rate: 2% of Face Weight       |
| <b>Maximum pile height</b> | -         | 0.1410 " (3.58 mm)                        |

|                                 | Standard     | Tarkett value                             |
|---------------------------------|--------------|---|
| <b>Stain Resistance</b>         | AATCC 175-08 | ≥8  |
| <b>Pile construction</b>        | -            | Patterned loop pile                       |
| <b>Surface Flammability</b>     | -            | PASS                                      |
| <b>Electrostatic Propensity</b> | -            | ≤ 3.0 kV                                  |
| <b>Gauge</b>                    | -            | 5/64"                                     |
| <b>Colorfastness to Light</b>   | AATCC 16E    | ≥ 4 after 100 hours                       |
| <b>Stitches/Rows per Inch</b>   | -            | 10 /in                                    |
| <b>Pile thickness</b>           | ASTM D5848   | 0.140 " (3.58 mm)                         |
| <b>Fiber System</b>             | -            | Dynex SD® Nylon (Stain resist)            |
| <b>Dye Method</b>               | -            | Solution dyed                             |
| <b>Secondary backing</b>        | -            | ethos® Modular with Omniccoat Technology™ |
| <b>Pattern repeat length</b>    | -            | 139.20 "                                  |
| <b>Pattern repeat width</b>     | -            | 72 "                                      |