

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Total thickness | - | 0.345 " (8.7 mm) |
| Fiber System | ISO 2424 | Dynex SD® Nylon (Stain resist) |
| Format Type | - | Tile |
| Construction Process | ISO 2424 | TUFTED |
| Installation method | - | Glue-Down |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Dye Method | - | Solution dyed |
| Product Material | - | Tufted |
| Cradle-to-Cradle | - | Silver |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|---------------------------------|----------|---------------------|
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Colorfastness to Light | - | ≥ 4 after 100 hours |
| Is cuttable | - | Yes |

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

| | Standard | Tarkett value |
|--|----------|--|
| Cradle-to-Cradle | - | Silver |
| Third Party Certification NSF-140 | - | Platinum |
| Antimicrobial Chemicals | - | No antimicrobials (EPA Registered pesticides) added to product |
| Post Consumer recycled content | - | 28 % |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|----------------------------|-----------|---|
| Total thickness | ASTM F386 | 0.345 " (8.7 mm) |
| Type of product | - | Textile Flooring |
| Pattern | - | Native Flora 11602 |
| Smoke Density | ASTM E662 | < 450 |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method | - | Glue-Down |
| Pattern type | - | Organic |
| Format Type | - | Tile |
| Soil protection | - | Application Rate: 2% of Face Weight |

| | Standard | Tarkett value |
|---------------------------------|--------------|--------------------------------|
| Maximum pile height | - | 0.1410 " (3.58 mm) |
| Stain Resistance | AATCC 175-08 | ≥8 |
| Pile construction | - | Patterned loop pile |
| Surface Flammability | - | PASS |
| Electrostatic Propensity | - | ≤ 3.0 kV |
| Gauge | - | 5/64" |
| Colorfastness to Light | AATCC 16E | ≥ 4 after 100 hours |
| Stitches/Rows per Inch | - | 10 /in |
| Fiber System | - | Dynex SD® Nylon (Stain resist) |
| Dye Method | - | Solution dyed |
| Secondary backing | - | ethos® Modular |
| Pattern repeat length | - | 46.40 " |
| Pattern repeat width | - | 72 " |