

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Fiber System | ISO 2424 | Dynex SD® Nylon (Stain resist) |
| Format Type | - | Tile |
| Construction Process | ISO 2424 | TUFTED |
| Installation method | - | Glue-Down |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Dye Method | - | Solution dyed |
| Product Material | - | Tufted |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------|----------|---------------|
| Is cuttable | - | No |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|-------------------------------|----------|---|
| Type of product | - | Textile Flooring |
| Pattern | - | Alight Edit 11613 |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method | - | Glue-Down |
| Pattern type | - | Linear |
| Format Type | - | Tile |
| Maximum pile height | - | 0.1410 " (3.58 mm) |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Stitches/Rows per Inch | - | 9.90 /in |
| Fiber System | - | Dynex SD® Nylon (Stain resist) |
| Dye Method | - | Solution dyed |
| Secondary backing | - | ethos® Modular |
| Pattern repeat length | - | 47.63 " |
| Pattern repeat width | - | 72 " |