

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CLASSIFICATION

|                   | Standard | Tarkett value                             |
|-------------------|----------|---|
| Surface treatment | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| Pattern           | -        | Connect Edit 11614                        |
| Pattern type      | -        | Geometric                                 |
| Format Type       | -        | Tile                                      |

### CHARACTERISTICS

|                      | Standard | Tarkett value                             |
|----------------------|----------|---|
| Pile thickness       | ISO 1766 | 0.075 " (1.85 mm)                         |
| Fiber System         | ISO 2424 | Dynex SD® Nylon (Stain resist)            |
| Format Type          | -        | Tile                                      |
| Box per pallet       | -        | 20  |
| Construction Process | ISO 2424 | TUFTED                                    |
| Installation method  | -        | Glue-Down                                 |
| Surface treatment    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing    | ISO 2424 | ethos® Modular with Omnicoat Technology™  |
| Dye Method           | -        | Solution dyed                             |
| Product Material     | -        | Tufted                                    |
| Pile construction    | -        | Patterned loop pile                       |
| Gauge                | -        | 5/64"                                     |

### TECHNICAL PERFORMANCE

|             | Standard | Tarkett value |
|-------------|----------|---------------|
| Is cuttable | -        | No            |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                        | Standard   | Tarkett value                             |
|------------------------|------------|---|
| Type of product        | -          | Textile Flooring                          |
| Pattern                | -          | Connect Edit 11614                        |
| Surface treatment      | -          | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method    | -          | Glue-Down                                 |
| Pattern type           | -          | Geometric                                 |
| Format Type            | -          | Tile                                      |
| Stitches/Rows per Inch | -          | 10 /in                                    |
| Pile thickness         | ASTM D5848 | 0.075 " (1.85 mm)                         |
| Maximum pile height    | -          | 0.1410 " (3.58 mm)                        |
| Fiber System           | -          | Dynex SD® Nylon (Stain resist)            |
| Dye Method             | -          | Solution dyed                             |

Standard

Tarkett value

|                              |   |   |
|------------------------------|---|---|
| <b>Secondary backing</b>     | - | ethos® Modular with Omniccoat Technology™ |
| <b>Pattern repeat length</b> | - | 135.30 "                                  |
| <b>Pattern repeat width</b>  | - | 72 "                                      |
| <b>Pile construction</b>     | - | Patterned loop pile                       |
| <b>Gauge</b>                 | - | 5/64"                                     |