

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

| | Standard | Tarkett value |
|-----------------------------|----------|---|
| Pile thickness | ISO 1766 | 0.070 " (1.78 mm) |
| Fiber System | ISO 2424 | Dynex SD® Nylon (Stain resist) |
| Format Type | - | Tile |
| Construction Process | ISO 2424 | TUFTED |
| Installation method | - | Glue-Down |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Secondary backing | ISO 2424 | ethos® Modular with Omnicoat Technology™ |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Dye Method | - | Solution dyed |
| Product Material | - | Tufted |

TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|--------------------|----------|---------------|
| Is cuttable | - | No |

CHARACTERISTICS & TECHNICAL PERFORMANCE

| | Standard | Tarkett value |
|-------------------------------|------------|---|
| Type of product | - | Textile Flooring |
| Pattern | - | Electric Edit 11611 |
| Surface treatment | - | Eco-Ensure(Fluorine-Free Soil Protection) |
| Installation method | - | Glue-Down |
| Pattern type | - | Organic |
| Format Type | - | Tile |
| Maximum pile height | - | 0.1870 " (4.75 mm) |
| Pile construction | - | Patterned loop pile |
| Gauge | - | 5/64" |
| Stitches/Rows per Inch | - | 10 /in |
| Pile thickness | ASTM D5848 | 0.070 " (1.78 mm) |
| Fiber System | - | Dynex SD® Nylon (Stain resist) |
| Dye Method | - | Solution dyed |
| Secondary backing | - | ethos® Modular with Omnicoat Technology™ |
| Pattern repeat length | - | 47.60 " |
| Pattern repeat width | - | 72 " |