

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CHARACTERISTICS

	Standard	Tarkett value
Pile thickness	ISO 1766	0.070 " (1.78 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Format Type	-	Tile
Construction Process	ISO 2424	TUFTED
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omnicoat Technology™
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Dye Method	-	Solution dyed
Product Material	-	Tufted

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	No

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Pattern	-	Electric Edit 11611
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Organic
Format Type	-	Tile
Maximum pile height	-	0.1870 " (4.75 mm)
Pile construction	-	Patterned loop pile
Gauge	-	5/64"
Stitches/Rows per Inch	-	10 /in
Pile thickness	ASTM D5848	0.070 " (1.78 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed
Secondary backing	-	ethos® Modular with Omnicoat Technology™
Pattern repeat length	-	47.60 "
Pattern repeat width	-	72 "