

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern	-	Edge Edit 11615
Pattern type	-	Geometric
Format Type	-	Tile

### CHARACTERISTICS

	Standard	Tarkett value
Pile thickness	ISO 1766	0.085 " (2.11 mm)
Fiber System	ISO 2424	Dynex SD® Nylon (Stain resist)
Format Type	-	Tile
Box per pallet	-	20
Construction Process	ISO 2424	TUFTED
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	ethos® Modular with Omniccoat Technology™
Dye Method	-	Solution dyed
Product Material	-	Tufted
Pile construction	-	Patterned loop pile
Gauge	-	5/64"

### TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	No

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Pattern	-	Edge Edit 11615
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Geometric
Format Type	-	Tile
Stitches/Rows per Inch	-	10 /in
Pile thickness	ASTM D5848	0.085 " (2.11 mm)
Maximum pile height	-	0.1870 " (4.75 mm)
Fiber System	-	Dynex SD® Nylon (Stain resist)
Dye Method	-	Solution dyed

	Standard	Tarkett value
<b>Secondary backing</b>	-	ethos® Modular with Omniccoat Technology™
<b>Pattern repeat length</b>	-	85.20 "
<b>Pattern repeat width</b>	-	72 "
<b>Pile construction</b>	-	Patterned loop pile
<b>Gauge</b>	-	5/64"