

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS

|                             | Standard | Tarkett value                             |
|-----------------------------|----------|---|
| <b>Pile thickness</b>       | ISO 1766 | 0.085 " (2.11 mm)                         |
| <b>Fiber System</b>         | ISO 2424 | Dynex SD® Nylon (Stain resist)            |
| <b>Format Type</b>          | -        | Tile                                      |
| <b>Construction Process</b> | ISO 2424 | TUFTED                                    |
| <b>Installation method</b>  | -        | Glue-Down                                 |
| <b>Box per pallet</b>       | -        | 20  |
| <b>Surface treatment</b>    | -        | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Secondary backing</b>    | ISO 2424 | ethos® Modular with Omnicoat Technology™  |
| <b>Pile construction</b>    | -        | Patterned loop pile                       |
| <b>Gauge</b>                | -        | 5/64"                                     |
| <b>Dye Method</b>           | -        | Solution dyed                             |
| <b>Product Material</b>     | -        | Tufted                                    |

### TECHNICAL PERFORMANCE

|                   | Standard | Tarkett value |
|-------------------|----------|---------------|
| <b>Is cutable</b> | -        | No            |

### CHARACTERISTICS & TECHNICAL PERFORMANCE

|                               | Standard   | Tarkett value                             |
|-------------------------------|------------|---|
| <b>Type of product</b>        | -          | Textile Flooring                          |
| <b>Pattern</b>                | -          | Edge Edit 11615                           |
| <b>Surface treatment</b>      | -          | Eco-Ensure(Fluorine-Free Soil Protection) |
| <b>Installation method</b>    | -          | Glue-Down                                 |
| <b>Pattern type</b>           | -          | Geometric                                 |
| <b>Format Type</b>            | -          | Tile                                      |
| <b>Maximum pile height</b>    | -          | 0.1870 " (4.75 mm)                        |
| <b>Pile construction</b>      | -          | Patterned loop pile                       |
| <b>Gauge</b>                  | -          | 5/64"                                     |
| <b>Stitches/Rows per Inch</b> | -          | 10 /in                                    |
| <b>Pile thickness</b>         | ASTM D5848 | 0.085 " (2.11 mm)                         |
| <b>Fiber System</b>           | -          | Dynex SD® Nylon (Stain resist)            |
| <b>Dye Method</b>             | -          | Solution dyed                             |
| <b>Secondary backing</b>      | -          | ethos® Modular with Omnicoat Technology™  |
| <b>Pattern repeat length</b>  | -          | 85.20 "                                   |
| <b>Pattern repeat width</b>   | -          | 72 "                                      |