

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Standard	Tarkett value
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Pattern	-	Cora H2834
Pattern type	-	Organic
Format Type	-	Roll

CHARACTERISTICS

	Standard	Tarkett value
Fiber System	ISO 2424	Lextron SD Nylon
Format Type	-	Roll
Construction Process	ISO 2424	TUFTED
Installation method	-	Glue-Down
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Secondary backing	ISO 2424	Super-Lok®
Dye Method	-	Solution dyed
Product Material	-	Tufted
Primary backing	-	Woven Polypropylene
Pile construction	-	Patterned loop pile
Gauge	-	1/10"

TECHNICAL PERFORMANCE

	Standard	Tarkett value
Is cuttable	-	Yes

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Textile Flooring
Length	-	1800 "
Width	-	144 "
Pattern	-	Cora H2834
Surface treatment	-	Eco-Ensure(Fluorine-Free Soil Protection)
Installation method	-	Glue-Down
Pattern type	-	Organic
Format Type	-	Roll
Stitches/Rows per Inch	-	10 /in
Minimum pile height	-	0.0620 " (1.57 mm)
Maximum pile height	-	0.2500 " (6.35 mm)
Fiber System	-	Lextron SD Nylon

	Standard	Tarkett value
Dye Method	-	Solution dyed
Secondary backing	-	Super-Lok®
Primary backing	-	Woven Polypropylene
Pile construction	-	Patterned loop pile
Gauge	-	1/10"